

m o o o i

## Perch Light Table

UMUT YAMAC



The Perch Light Table Lamp, the smallest of its family, holds its own particular charm. You may admire the details of its delicate beauty and follow the light swinging of the bird from nearby, while comfortably seated. What's more, you can easily set it in motion with a gentle touch of your hand while enjoying its warm sunny glow.

---

### *Detailing*



What is more poetic and elegantly captivating than a bird perched on a branch, flirting, singing and celebrating life?

---

### *Colours*

Brass and white

# Perch Light Table

## Dimensions

22cm | 8.7"



25cm | 9.8"



61,5cm | 24.2"

## Product

**WIDTH** 22cm | 8.7"  
**HEIGHT** 61.5cm | 24.2"  
**DEPTH** 25cm | 9.8"  
**WEIGHT NETTO** 4kg | 8.82lbs

## Packaging

**WIDTH** 34cm | 13.4"  
**HEIGHT** 26cm | 10.2"  
**CUBAGE** 0.05m<sup>3</sup> | 1.94ft<sup>3</sup>  
**LENGTH** 62cm | 24.4"  
**WEIGHT** 4kg | 8.82lbs

## Technical CE

### MATERIAL

Steel and aluminium frame with polypropylene (PP) and synthetic paper bird .

### ENERGY LABEL

Energy Label B

### LIGHTSOURCE TYPE

LED

### LIGHTSOURCE INCLUDED

Yes

### NUMBER OF LIGHTSOURCES

1

### INPUT VOLTAGE

90-264

### FREQUENCY

50/60

### MAX POWER CONSUMPTION

5W

### DIMMABLE

No

### LAMPHOLDER

LED (Solid state)

### LIFETIME

50000 hours

### CABLE COLOUR

Black

### PLUG TYPE

Europlug (Type-C)

### CABLE LENGTH

300cm | 118.1"

### SWITCH

In line on/off switch

### COLOUR TEMPERATUE

3000 K

### CRI

80

### LIGHT DIRECTION

All directions

### LIGHT OUTPUT

90 lm

## Technical cULus

**MATERIAL**

Steel and aluminium frame with polypropylene (PP) and synthetic paper bird .

**ENERGY LABEL**

Energy Label B

**LIGHTSOURCE TYPE**

LED

**LIGHTSOURCE INCLUDED**

Yes

**NUMBER OF LIGHTSOURCES**

1

**INPUT VOLTAGE**

100-240

**FREQUENCY**

50/60

**MAX POWER CONSUMPTION**

5W

**DIMMABLE**

No

**LAMPHOLDER**

LED (Solid state)

**LIFETIME**

50000 hours

**CABLE COLOUR**

Black

**PLUG TYPE**

US plug (Type A)

**CABLE LENGTH**

300cm | 118.1"

**SWITCH**

In line on/off switch

**COLOUR TEMPERATUE**

3000 K

**CRI**

80

**LIGHT DIRECTION**

All directions

**LIGHT OUTPUT**

90 lm