

FLOS

Noctambule S3 Low Cylinder and Bowl - Specification Sheet by Konstantin Grcic, 2019

Mounting	Suspension
Lamp (Bulb) Description	54W 1579lm -2700K - CRI 90
Canopy Dimension	Diameter 7.3" - 1.8" High
Environment	Indoor - Dry Location
Dimming	Active 0-10V/DALI/Push Button
Technical and Product Description	Noctambule is an innovative lighting system with a transparent hand-blown glass cylinder, surrounded on both top and bottom by discrete LED technology. The fixtures built from these units form columns of light at varying heights that illuminate at the intersection between each module.

Configurable as a hanging or standing lamp, Noctambule features additional components that allow for numerous options. The cylindrical body is available at a low and high height, and a dome- or cone-shaped head can be selected if a more direct light source is desired. Dimming capabilities can be configured in the power supply unit within the ceiling rose, or as a pedal-operated panel on the power cord.


The followings are the only compatible dimmers (not included).

- 0-10V Wall dimmer (hardwire from fixture to dimmer)**
Crestron - CLW-DIMFLVEX-P-A-S
- Casambi wall dimmer (wireless from fixture to dimmer)**
Mcowng - PSC-DM-WS-100-BLE-CB with Casambi module CBU-ADSR and LV004-12-UNV2D
- 0-10V interface and Module**
Lutron RF Dimming Module - LMJ-5T-DV-
Lutron Vive PowPak - RMJS-8T-DV-
Lutron GRX-TVM2
Crestron DIN-A08
Crestron GL-CAEN-2DIMFLV8
Crestron CLX-2DIMFLV8
- Wireless 0-10V Casambi (control via Casambi app)**
CBU-ADSR with LV004-12-UNV2D
- Other dimmer manufacturers**
The client must consult with dimmer and interface manufacturers if Interface or Module provides **0-10V Sourcing current**.



F0274000

Dimensional Image



Certifications



Electrical

Voltage	100-240V
IP Rating	IP20

Physical

Cord Length (inches)	157,48"
Construction Material	Die-cast aluminum, Blown crystal
Weight	39 lbs